



Type MIL C-17		RG 11 A/U	RG 34 B/U	RG 58 C/U	RG 59 B/U	RG 174 U	RG 213 U	RG 218 U	RG 220 U
Inner conductor	Formation	7 x 0,40	7 x 0,63	19 x 0,18	1 x 0,58	7 x 0,16	7 x 0,75	1 x 4,95	1 x 6,60
	Material	TC	C	TC	CW	CW	C	C	C
Dielectric	Material	PE	PE	PE	PE	PE	PE	PE	PE
	Ø mm	7,25	11,70	2,95	3,70	1,55	7,25	17,30	23,10
Braided Screening		C	C	TC	C	TC	C	C	C
Jacket	Material	PVC	PVC	PVC	PVC	PVC	PVC	PVC	PVC
	Ø mm	10,30	16,00	4,95	6,15	2,55	10,30	22,10	28,40
	Color	Black	Black	Black	Black	Black	Black	Black	Black
Rated Weight Kg/km		145	330	41	55	12	162	700	1130
Nominal Impedance ± 4% Ohm		75	75	50	75	50	50	50	50
Capacit. ± 8% pF/m		67	67	100	67	100	100	100	100
Velocity Ratio %		66,5	66,5	66,5	66,5	66,5	66,5	66,5	66,5
Nominal Attenuation db/100 m a MHz	10	2,15	1,00	4,60	3,60	12,80	1,80	0,79	0,55
	100	7,5	4,60	16,10	11,20	29,20	6,20	3,10	2,30
	400	15,80	10,80	39,40	23,00	57,40	13,50	7,85	6,05
	1000	25,50	19,00	78,70	39,40	98,50	26,30	14,40	11,75
	3000	54,00	52,50	177,00	86,90	210,00	52,50	31,20	25,30