



Type MIL C-17		RG 6 A/U	RG 214 U	RG 216 U	RG 217 U	RG 223 U		
Inner conductor	Formation	1 x 0,72	1 x 0,75	7 x 0,40	1 x 2,70	1 x 0,90		
	Material	CW	SC	TC	C	SC		
Dielectric	Material	PE	PE	PE	PE	PE		
	Ø mm	4,70	7,25	7,25	9,40	2,95		
Braided Screening	1°	SC	SC	C	C	SC		
	2°	C	SC	C	C	SC		
Jacket	Material	PVC	PVC	PVC	PVC	PVC		
	Ø mm	8,45	10,80	10,80	13,80	5,50		
	Color	Black	Black	Black	Black	Black		
Rated Weight Kg/km		120	210	197	330	60		
Nominal Impedance ± 4% Ohm		75	50	75	50	50		
Capacit. ± 8% pF/m		67	100	67	100	100		
Velocity Ratio %		66,5	66,5	66,5	66,5	66,5		
Nominal Attenuation db/100 m a MHz	10	2,70	2,15	2,15	1,35	3,90		
	100	8,85	7,55	7,55	4,60	15,80		
	400	19,40	16,40	15,80	10,15	32,80		
	1000	32,20	26,90	25,60	18,00	54,10		
	3000	75,50	59,00	54,00	40,70	100,00		