



Type MIL C-17	2xRG 59 B/U	3xRG 59 B/U	4xRG 59 B/U	5xRG 59 B/U	6xRG 59 B/U	8xRG 59 B/U	10xRG 59 B/U	12xRG 59 B/U	20xRG 59 B/U	
Single cable dimensions	Ref. RG 59 B/U									
Foil	Polyester									
Jacket	Material	PVC	PVC	PVC	PVC	PVC	PVC	PVC	PVC	PVC
	Ø mm	6,1 x 12,5	16,00	17,80	19,30	21,00	23,00	24,70	29,00	34,00
	Color	Black	Black	Black	Black	Black	Black	Black	Black	Black
Rated Weight Kg/km	255	314	385	453	525	620	965	1158	1750	
Nominal Impedance ± 4% Ohm	75	75	75	75	75	75	75	75	75	
Capacit. ± 8% pF/m	67	67	67	67	67	67	67	67	67	
Velocity Ratio %	66,5	66,5	66,5	66,5	66,5	66,5	66,5	66,5	66,5	
Nominal Attenuation db/100 m a MHz	10	3,60	3,60	3,60	3,60	3,60	3,60	3,60	3,60	
	100	11,20	11,20	11,20	11,20	11,20	11,20	11,20	11,20	
	400	23,00	23,00	23,00	23,00	23,00	23,00	23,00	23,00	
	1000	39,40	39,40	39,40	39,40	39,40	39,40	39,40	39,40	
	3000	86,90	86,90	86,90	86,90	86,90	86,90	86,90	86,90	